

WALSIN TECHNOLOGY CORPORATION

Change Notification

CN No.: CN-C180501	<input type="checkbox"/> Material	<input type="checkbox"/> Process																																																					
	<input type="checkbox"/> Specification	<input checked="" type="checkbox"/> Others																																																					
Subject : End of Life Notice for Y5V MLCC Hi-Cap. product.																																																							
Reasons : In order to maximize our MLCC production efficiency and enhance production flexibility, we decide to phase out partial Y5V items.																																																							
Contents: Phase out items:																																																							
	<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th style="width:15%;">Series</th> <th style="width:15%;">Size</th> <th style="width:20%;">Rated voltage</th> <th style="width:50%;">EOL PN.</th> </tr> </thead> <tbody> <tr> <td rowspan="20" style="text-align: center; vertical-align: middle;">General Purpose Caps. (Y5V)</td> <td rowspan="2" style="text-align: center;">0402</td> <td style="text-align: center;">16V</td> <td>0402F154_160 0402F184_160 0402F224_160 0402F334_160 0402F474_160</td> </tr> <tr> <td style="text-align: center;">6.3V</td> <td>0402F684_6R3</td> </tr> <tr> <td rowspan="6" style="text-align: center;">0603</td> <td style="text-align: center;">50V</td> <td>0603F334_500 0603F474_500</td> </tr> <tr> <td style="text-align: center;">25V</td> <td>0603F684_250 0603F105_250</td> </tr> <tr> <td style="text-align: center;">16V</td> <td>0603F225_160</td> </tr> <tr> <td style="text-align: center;">10V</td> <td>0603F475_100</td> </tr> <tr> <td style="text-align: center;">6.3V</td> <td>0603F475_6R3</td> </tr> <tr> <td rowspan="4" style="text-align: center;">0805</td> <td style="text-align: center;">25V</td> <td>0805F225_250 0805F475_250</td> </tr> <tr> <td style="text-align: center;">16V</td> <td>0805F106_160</td> </tr> <tr> <td style="text-align: center;">10V</td> <td>0805F226_100</td> </tr> <tr> <td style="text-align: center;">6.3V</td> <td>0805F226_6R3</td> </tr> <tr> <td rowspan="4" style="text-align: center;">1206</td> <td style="text-align: center;">50V</td> <td>1206F225_500 1206F475_500</td> </tr> <tr> <td style="text-align: center;">25V</td> <td>1206F106_250</td> </tr> <tr> <td style="text-align: center;">16V</td> <td>1206F226_160</td> </tr> <tr> <td style="text-align: center;">6.3V</td> <td>1206F476_6R3</td> </tr> <tr> <td style="text-align: center;">1210</td> <td style="text-align: center;">50V</td> <td>1210F685_500 1210F106_500</td> </tr> <tr> <td style="text-align: center;">1812</td> <td style="text-align: center;">50V</td> <td>1812F106_500</td> </tr> <tr> <td rowspan="3" style="text-align: center;">Low profile Caps. (Y5V)</td> <td rowspan="3" style="text-align: center;">0805</td> <td style="text-align: center;">50V</td> <td>TT21F105_500</td> </tr> <tr> <td style="text-align: center;">16V</td> <td>TT21F475_160</td> </tr> <tr> <td style="text-align: center;">10V</td> <td>TT21F106_100</td> </tr> </tbody> </table>	Series	Size	Rated voltage	EOL PN.	General Purpose Caps. (Y5V)	0402	16V	0402F154_160 0402F184_160 0402F224_160 0402F334_160 0402F474_160	6.3V	0402F684_6R3	0603	50V	0603F334_500 0603F474_500	25V	0603F684_250 0603F105_250	16V	0603F225_160	10V	0603F475_100	6.3V	0603F475_6R3	0805	25V	0805F225_250 0805F475_250	16V	0805F106_160	10V	0805F226_100	6.3V	0805F226_6R3	1206	50V	1206F225_500 1206F475_500	25V	1206F106_250	16V	1206F226_160	6.3V	1206F476_6R3	1210	50V	1210F685_500 1210F106_500	1812	50V	1812F106_500	Low profile Caps. (Y5V)	0805	50V	TT21F105_500	16V	TT21F475_160	10V	TT21F106_100	
Series	Size	Rated voltage	EOL PN.																																																				
General Purpose Caps. (Y5V)	0402	16V	0402F154_160 0402F184_160 0402F224_160 0402F334_160 0402F474_160																																																				
		6.3V	0402F684_6R3																																																				
	0603	50V	0603F334_500 0603F474_500																																																				
		25V	0603F684_250 0603F105_250																																																				
		16V	0603F225_160																																																				
		10V	0603F475_100																																																				
		6.3V	0603F475_6R3																																																				
		0805	25V	0805F225_250 0805F475_250																																																			
	16V		0805F106_160																																																				
	10V		0805F226_100																																																				
	6.3V		0805F226_6R3																																																				
	1206	50V	1206F225_500 1206F475_500																																																				
		25V	1206F106_250																																																				
		16V	1206F226_160																																																				
		6.3V	1206F476_6R3																																																				
	1210	50V	1210F685_500 1210F106_500																																																				
	1812	50V	1812F106_500																																																				
	Low profile Caps. (Y5V)	0805	50V	TT21F105_500																																																			
			16V	TT21F475_160																																																			
			10V	TT21F106_100																																																			
Description : X5R/X7R product was recommended to replace above Y5V hi-cap MLCC																																																							
Effective Date: Nov 18, 2018	Prepared by : CT Chuang/FAE manager																																																						
Issued By: Lee Ku/President (May 18, 2018)	To : <input checked="" type="checkbox"/> Customer : All <input checked="" type="checkbox"/> WTC Q&R : Jay Huang cc : <input checked="" type="checkbox"/> WTC Sales : All																																																						
Feedback by Customer :	<input type="checkbox"/> Accept for all PN Parts <input type="checkbox"/> Accept for Own Brand PN of AVL, except OEM's PN of AVL <input type="checkbox"/> Reject, Reason:																																																						
(Please note the name of person in charge and autograph signed back is preferred.)	(Please kindly feedback before <u>Oct. 18, 2018</u> , otherwise the change will be effective since. <u>Nov. 18, 2018</u>)																																																						