



| Title of Change: | Qualification of Lead Frame raw material change used in the ON Semiconductor SSOP16, TSSOP20 (225mil), SSOP24, SSOP30 and TSSOP36 (275mil) package types. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|---------------------|------------------|---------------|--|---------------------|------------------|-----------------------|--|--|--|----------------------------------|----------------------|------|------|----------------------|---------|-----|-----|------------------------|-----|-------|-------|-------------------------|-------|----|----|--------------------|--------------------|-----|-----|---------------------|--|--|--|----|---|--------|--------|----|---|-------------|----------|----|---|----------|----------|----|---|-------------|----------|---|---|-------------|----------|----|---|------|-------------|----|---|------|-------------|
| Proposed first ship date: | 3 November 2016 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Contact information: | Contact your local ON Semiconductor Sales Office or <Takeshi2.Hoshino@onsemi.com>,<Yutaka.Okamura@onsemi.com>,<Takehito.Tsukui@onsemi.com>,<Shuichi.Takahashi@onsemi.com>,<Naoki.Koyama@onsemi.com>,<Shinya.Okada@onsemi.com>,<Ikuro.Saeki@onsemi.com>,<Hiroshi.Kojima@onsemi.com>,<Tetsuya.Fukushima@onsemi.com> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Samples: | Contact your local ON Semiconductor Sales Office | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Additional Reliability Data: | Contact your local ON Semiconductor Sales Office | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Type of notification: | This is a Final Product/Process Change Notification (FPCN) sent to customers. FPCNs are issued 90 days prior to implementation of the change. ON Semiconductor will consider this change accepted, unless an inquiry is made in writing within 30 days of delivery of this notice. To do so, contact <PCN.Support@onsemi.com>. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Change Part Identification: | Affected products will be identified with date code. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Change category: | <input type="checkbox"/> Wafer Fab Change <input checked="" type="checkbox"/> Assembly Change <input type="checkbox"/> Test Change <input type="checkbox"/> Other _____ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Change Sub-Category(s): | <input type="checkbox"/> Manufacturing Site Change/Addition <input checked="" type="checkbox"/> Material Change <input type="checkbox"/> Datasheet/Product Doc change <input type="checkbox"/> Manufacturing Process Change <input type="checkbox"/> Product specific change <input type="checkbox"/> Shipping/Packaging/Marking <input type="checkbox"/> Other: _____ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Sites Affected: | <input type="checkbox"/> All site(s) <input type="checkbox"/> not applicable <input checked="" type="checkbox"/> ON Semiconductor site(s) : ON Tarlac City, Philippines <input type="checkbox"/> External Foundry/Subcon site(s) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Description and Purpose: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>This is a Final Process Change Notice to announce the replacement of existing lead frame raw material from C50710 to C19400 (C50710/C19400: ASTM code). The reason is that the existing lead frame raw material will no longer be available.</p> <p>The table below shows comparison of mechanical and chemical properties between the two materials.</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th>Material Name</th> <th></th> <th>C19400(Alternative)</th> <th>C50710(Existing)</th> </tr> </thead> <tbody> <tr> <td colspan="4" style="text-align: center;">Mechanical properties</td> </tr> <tr> <td>Coefficient of Thermal Expansion</td> <td>X10⁻⁸/K</td> <td>17.6</td> <td>17.0</td> </tr> <tr> <td>Thermal Conductivity</td> <td>W (m·K)</td> <td>262</td> <td>155</td> </tr> <tr> <td>Electrical Resistivity</td> <td>μΩm</td> <td>0.025</td> <td>0.054</td> </tr> <tr> <td>Electrical Conductivity</td> <td>%IACS</td> <td>65</td> <td>32</td> </tr> <tr> <td>Modulus Elasticity</td> <td>KN/mm²</td> <td>121</td> <td>125</td> </tr> <tr> <td colspan="4" style="text-align: center;">Chemical properties</td> </tr> <tr> <td>Cu</td> <td>%</td> <td>Remain</td> <td>Remain</td> </tr> <tr> <td>Zn</td> <td>%</td> <td>0.05 ~ 0.20</td> <td>Max 0.20</td> </tr> <tr> <td>Pb</td> <td>%</td> <td>Max 0.03</td> <td>Max 0.02</td> </tr> <tr> <td>Fe</td> <td>%</td> <td>2.10 ~ 2.60</td> <td>Max 0.10</td> </tr> <tr> <td>P</td> <td>%</td> <td>0.01 ~ 0.15</td> <td>Max 0.15</td> </tr> <tr> <td>Sn</td> <td>%</td> <td>None</td> <td>1.70 ~ 2.30</td> </tr> <tr> <td>Ni</td> <td>%</td> <td>None</td> <td>0.10 ~ 0.40</td> </tr> </tbody> </table> | | | | Material Name | | C19400(Alternative) | C50710(Existing) | Mechanical properties | | | | Coefficient of Thermal Expansion | X10 ⁻⁸ /K | 17.6 | 17.0 | Thermal Conductivity | W (m·K) | 262 | 155 | Electrical Resistivity | μΩm | 0.025 | 0.054 | Electrical Conductivity | %IACS | 65 | 32 | Modulus Elasticity | KN/mm ² | 121 | 125 | Chemical properties | | | | Cu | % | Remain | Remain | Zn | % | 0.05 ~ 0.20 | Max 0.20 | Pb | % | Max 0.03 | Max 0.02 | Fe | % | 2.10 ~ 2.60 | Max 0.10 | P | % | 0.01 ~ 0.15 | Max 0.15 | Sn | % | None | 1.70 ~ 2.30 | Ni | % | None | 0.10 ~ 0.40 |
| Material Name | | C19400(Alternative) | C50710(Existing) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Mechanical properties | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Coefficient of Thermal Expansion | X10 ⁻⁸ /K | 17.6 | 17.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Thermal Conductivity | W (m·K) | 262 | 155 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Electrical Resistivity | μΩm | 0.025 | 0.054 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Electrical Conductivity | %IACS | 65 | 32 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Modulus Elasticity | KN/mm ² | 121 | 125 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Chemical properties | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cu | % | Remain | Remain | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Zn | % | 0.05 ~ 0.20 | Max 0.20 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pb | % | Max 0.03 | Max 0.02 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Fe | % | 2.10 ~ 2.60 | Max 0.10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| P | % | 0.01 ~ 0.15 | Max 0.15 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Sn | % | None | 1.70 ~ 2.30 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Ni | % | None | 0.10 ~ 0.40 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Reliability Data Summary: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |



QV DEVICE NAME : LV8860V-TLM-H

PACKAGE : SSOP16

| Test | Specification | Condition | Interval | Results |
|------|-------------------|---------------------|----------|---------|
| HTSL | JEITA ED-4701/200 | Ta=150°C | 1008 hrs | 0/22 |
| AC | JEITA ED-4701-3 | Ta=121°C , 15psig | 96 hrs | 0/22 |
| TC | JEITA ED-4701/100 | Ta= -65°C to +150°C | 100 cyc | 0/22 |
| SD | JEITA ED-4701/301 | Ta = 245°C , 5 sec | - | PASS |
| PC | JEITA ED-4701/300 | MSL 3 @ 260 °C | 2 times- | PASS |

QV DEVICE NAME : LV23401V-N-TLM-H

PACKAGE : SSOP30

| Test | Specification | Condition | Interval | Results |
|------|-------------------|---------------------|----------|---------|
| HTSL | JEITA ED-4701/200 | Ta=150°C | 1008 hrs | 0/22 |
| AC | JEITA ED-4701-3 | Ta=121°C , 15psig | 96 hrs | 0/22 |
| TC | JEITA ED-4701/100 | Ta= -65°C to +150°C | 100 cyc | 0/22 |
| SD | JEITA ED-4701/301 | Ta = 245°C , 5 sec | - | PASS |
| PC | JEITA ED-4701/300 | MSL 3 @ 260 °C | 2 times- | PASS |

QV DEVICE NAME : LB1939T-MPB-E

PACKAGE : TSSOP20

| Test | Specification | Condition | Interval | Results |
|------|-------------------|---------------------|----------|---------|
| HTSL | JEITA ED-4701/200 | Ta=150°C | 1008 hrs | 0/22 |
| AC | JEITA ED-4701-3 | Ta=121°C , 15psig | 96 hrs | 0/22 |
| TC | JEITA ED-4701/100 | Ta= -65°C to +150°C | 100 cyc | 0/22 |
| SD | JEITA ED-4701/301 | Ta = 245°C , 5 sec | - | PASS |
| PC | JEITA ED-4701/300 | MSL 3 @ 260 °C | 2 times- | PASS |

Electrical Characteristic Summary:

Electrical characteristics are not impacted.



| List of affected Standard Parts: | |
|----------------------------------|-----------------------|
| Part Number | Qualification Vehicle |
| LB11600JV-TLM-E | LV23401V-N-TLM-H |
| LC72720YVS-TLM-E | LV23401V-N-TLM-H |
| LC72725KVS-H | LV8860V-TLM-H |
| LC75700TS-TLM-E | LB1939T-MPB-E |
| LC75700T-TLM-E | LB1939T-MPB-E |
| LC75814VS-TLM-E | LV23401V-N-TLM-H |
| LC75814V-TLM-E | LV23401V-N-TLM-H |
| LV3327PV-TLM-H | LV8860V-TLM-H |